

# Datasheet Conveyor Belt



**NITTA CORPORATION  
OF HOLLAND**

Berenkoog 25  
1822 BH Alkmaar  
The Netherlands

T: +31 (0)72 562 22 34  
F: +31 (0)72 561 32 38

E: sales@nitta.nl  
www.nittacorporation.com

- **NITTA BELT TYPE:**  
**2 RF 72 ST IM**
- **Nitta Japan code:**



**Construction:** 2 plies polyester, rigid

	TOP COVER	INNER LAYER	BOTTOM SIDE	
<b>Material:</b>	PVC	PVC	Impregnated fabric	
<b>Thickness:</b>	2		-	<b>mm (approx.)</b>
<b>Colour:</b>	White	White	-	
<b>Hardness:</b>	55 Shore A		-	
<b>Profile:</b>	ST		-	

<b>Total thickness:</b>	5,3	<b>mm (approx.)</b>
<b>Weight:</b>	5,3	<b>kg/m<sup>2</sup> (approx.)</b>
<b>Max. width:</b>	2000	<b>mm</b>
<b>Belt support:</b>	Sliderbed (Rollers), Flat	

<b>Rating at 1% elongation:</b>	10	<b>N/mm</b>
<b>Advised pretension:</b>	4 - 7	<b>N/mm</b>
<b>Maximum allowable tension:</b>	20	<b>N/mm</b>
<b>Temperature range:</b>	-10 to +90	<b>°C</b>
<b>Minimum pulley diameters:</b>		
<b>Flexing:</b>	70	<b>mm</b>
<b>Backflexing:</b>	90	<b>mm</b>

**Special approval:** FDA, 10/2011/EC + amendments

**Applications:** Conveyor belt for the food industry  
Conveying of meat, fish and poultry products  
Inclined or declined conveyors  
Oil and grease resistant

Date of issue 02-04-2014-1

Your Partner In Belting Solutions

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nittacorporation.com