

Datasheet Conveyor Belt




NITTA CORPORATION OF HOLLAND

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
2 CF
- **Nitta Japan code:**
CC-12DKC



Construction: 2 plies cotton/polyester, non-rigid

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	Cotton/polyester fabric	PVC	Cotton/polyester fabric	
Thickness:	-		-	mm (approx.)
Colour:	-	White	-	
Hardness:	-		-	
Profile:	-		-	

Total thickness:	1,8	mm (approx.)
Weight:	1,9	kg/m² (approx.)
Max. width:	2000	mm
Belt support:	Sliderbed (Rollers), Flat/trough	

Rating at 1% elongation:	8	N/mm
Advised pretension:	4 - 7	N/mm
Maximum allowable tension:	17	N/mm
Temperature range:	-10 to +90	°C

Minimum pulley diameters:		
Flexing:	20	mm
Backflexing:	20	mm

Special approval: FDA, 10/2011/EC + amendments

Applications:

- Conveyor belt in bakeries
- Excellent release of dough in bakeries
- Conveying of (un)vulcanised rubber
- In laundries
- In the leather industry

Date of issue 01-04-2014-1

Your Partner In Belting Solutions

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nittacorporation.com