

Datasheet Conveyor Belt



**NITTA CORPORATION
OF HOLLAND**

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:
2 LRWAF 907 SQPR**
- **Nitta Japan code:**



Construction: 2 plies polyester, rigid, antistatic

	TOP COVER	INNER LAYER	BOTTOM SIDE
Material:	PVC	PVC	Whisper antistatic fabric
Thickness:	0,7	-	mm (approx.)
Colour:	Black	Black	-
Hardness:	80 Shore A	-	-
Profile:	SQPR	-	-

Total thickness: 2,7 mm (approx.)
Weight: 2,8 kg/m² (approx.)
Max. width: 3000 mm
Belt support: Sliderbed (Rollers), Flat

Rating at 1% elongation: 10 N/mm
Advised pretension: 4 - 7 N/mm
Maximum allowable tension: 18 N/mm
Temperature range: -10 to +80 °C

Minimum pulley diameters:
Flexing: 50 mm
Backflexing: 75 mm

Special approval: Not applicable

Applications: General purpose conveying
Jogging machines (treadmills)

Date of issue 08-01-2015-1

Your Partner In Belting Solutions

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nittacorporation.com